

COM100D-EU

The COM100D-EU Smart Communication Box integrates the hardware and software functions of Logger1000A-EU, supporting various networking connection possibilities. It is a highly reliable package with dedicated SPDs and IP66, suitable for outdoor installation



FLEXIBLE NETWORKING

- Supports RS485, Ethernet, 4G, WLAN communication
- Supports energy meter, environmental sensors and multiple inverters



EASY OPERATION

- Night light for maintenance
- Robust enclosure, easy to install



CONVENIENT O&M

- Inverter batch parameter settings and firmware updates
- PV Plant maintenance via remote Web access for optimized OPEX
- Active and reactive power control



Technical parameters	COM100D-EU
Basic data	
Supported device number	Max. 30
Communication	
RS485 interface	3
Ethernet	1 * RJ45, 10/100/1000 Mbps
Digital input	5, Max. 24 Vdc
Analog input	4, support 4 mA - 20 mA or 0 Vdc - 10 Vdc
SIM Card *	Micro-Sim (15 mm * 12 mm)
Operation band	LTE (FDD): B1 / B3 / B7 / B8 / B20 / B28A LTE (TDD): B38 / B40 / B41 GSM: B3 / B8
WLAN	802.11 a/b/g/n/ac, HT20/40/80 MHz, 2.4 GHz / 5 GHz
4G antenna	On-board antenna
Power supply	
AC input	100 Vac - 277 Vac, 50 Hz / 60 Hz
DC output	24 ± 0.72 VDC, 0.5 A
Power consumption	Typ. 30 W, Max. 40 W
Night LED for O&M	< 1 W
Ambient conditions	
Operating temperature	-30 °C - 60 °C
Allowable relative humidity range	0 % - 95 %, non-condensing
Max. operating altitude	4000 m
Protection class	IP66
Mechanical parameters	
Dimensions (W * H * D)	460 mm * 315 mm * 126 mm
Weight	4.9 kg
Installation	Wall mounted, Bracket mounted, Pole mounted, outdoor and indoor
Standard compliance	
EMC and Radio	CE, UKCA

* Please refer to the user manual for further instructions and information on compatible SIM card providers

